PU FEST 2K CARBON

Water-based two-component sealer for microcement and resin floors

DESCRIPTION

PU FEST 2K CARBON is a waterborne two-component sealer designed to protect and finish microcement and resin floors. Thanks to its polycarbonate-based formula, it offers high hardness, abrasion resistance, and a smooth surface finish. It is suitable for both residential and commercial spaces - wherever durability matters.

APPLICATION

PU FEST 2K CARBON can be used for:

- · protecting microcement surfaces
- protecting epoxy and polyurethane resin coatings, as well as cement-based coatings on floors and walls.

Product for professional use only.

TECHNICAL DATA

• Mixing ratio (100:8):

100 parts by weight of A: 8 parts by weight of B

- Color: transparent, colorless
- Application temperature: +15°C ÷ +25°C
- Touch dry: 1-2 hours (depending on temperature)
- Light foot traffic: after 24 hours, full curing - after 7 days
- Consumption: 0.07-0.15 kg/m² per coat
- Finish: matt, satin haptic
- Pot life after mixing: 45-60 minutes
- Shelf life: 12 months

HOW TO USE

The surface must be fully cured, sound, dry, clean, and free from dust, waxes, and oils. Shake Component A of PU FEST 2K CARBON sealer thoroughly before use. Add Component B according to the ratio specified on the packaging. Mix Component A and Component B in a 100:8 ratio by weight (100 parts A: 8 parts B). Apply using a high-quality roller with 7-9 mm pile length.

The second coat of PU FEST 2K CARBON can be applied:

- 2 after hours without sanding,
- or after 24 hours with light sanding using 220-grit sandpaper.

PACKAGING

PU FEST 2K CARBON is supplied in the following sets:

- 5 kg of Component A + 0.4 kg of Component B = 5.4 kg total
- 1000 g of Component A + 80 g of Component B = 1080 g total

@festfloor





Do not apply the sealer during the hottest hours of the day, in unfavorable weather conditions, or on damp substrates.

SAFETY MEASURES

COMPONENT A:

- Causes serious eye irritation.
- Wear protective gloves / clothing / eye and face protection.
- In case of contact with eyes, seek medical advice immediately.
- EUH208

Contains biocidal product: mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). Also contains 1,2-benzisothiazol-3(2H)-one.

COMPONENT B:

- Harmful if inhaled.
- May cause respiratory irritation.
- May cause an allergic skin reaction.
- Harmful to aquatic life with long-lasting effects.
- Wear protective gloves.
- Avoid breathing dust / fumes / gas / mist / vapors / spray.
- If feeling unwell, contact a POISON CENTER or doctor.
- Store in a well-ventilated place.
- Keep container tightly closed.
- Remove contaminated clothing and wash before reuse.







